

**Turned Aluminium Tilt
DLL701**



**Turned Aluminium Tilt
DLL902**



**3 x Turned Aluminium Tilt
DLL823**



Features DLL701, 902, 823

Turned aluminium

DLL823: 3 x MR11, suitable for large cutouts

Voltage: 12 Volts

Maximum Wattage: 35W per lamp

Lamp Type: MR11

Lamp Base: GU4

Supplied with 300mm flying leads


Guarantee: 5 Year

Related Products

Lamp: LMR11353K (MR11 35W 24 deg, 3,000hr)

Downlight: DLL711, 712, 713, 714, 912

**3W 700mA Module
LED223**



Converts a MR11 turned
Aluminium Downlight to LED

Specifications

	DLL701	DLL902	DLL823
Colour	Alum. 'AL'	Alum. 'AL'	Alum. 'AL'
Overall	76 x 76mm	78mm	160mm
Cut-out	66mm	66mm	144mm
Recess	70mm	70mm	70mm
Tilt	30 Deg.	30 Deg.	30 Deg.
Rotation	350 Deg.	350 Deg.	350 Deg.
Projection	2mm	2mm	2mm
IP	20	20	20

NZECP54

	DLL701	DLL902	DLL823
SBC	75mm	75mm	75mm
HCB	100mm	100mm	100mm
NZECP54 Classification	CS	CS	CS
Moisture Transfer	C	C	C
Thermal insulation class	S 100mm	S 100mm	S 100mm
Upgrade CS to CA	HC11	HC11	HC11 x 3

Approvals



NZECP54

SBC: Min. height from combustible material

HCB: Min. height clearance from top of lamp holder

NZECP54 Classification: Recessed luminaire Classification NZECP54

Moisture Transfer: Luminaire moisture transfer category

Thermal insulation class: Thermal insulation clearance class

CS Classification upgraded to CA when used with appropriate Heat Can